



# APPROVAL OF MANUFACTURER CERTIFICATE

Certificate No:  
**AMMM000026W**  
Revision No:  
**1**

This is to certify:

That  
**Bodega G. & C. S.p.A.**  
Via Binda di Sopra, 1 - 24034 Cisano Bergamasco (BG),  
Italy

is an approved manufacturer of  
**Wrought Aluminium and Aluminium Alloys**

in accordance with  
**DNV GL rules for classification – Ships**

and the following particulars:

<b>Application area</b>	<b>Wrought Aluminium Alloys</b>
<b>Product</b>	<b>Sections</b>
<b>Manufacturing method</b>	<b>Extruded</b>
<b>Max. wall thickness</b>	<b>See page 2</b>
<b>Temper/Heat treatment condition</b>	<b>See page 2</b>
<b>Dimensions</b>	<b>See page 2</b>

Manufacturer(s) approved by this certificate is/are accepted to deliver according to DNV GL, DNV and GL rules.  
Materials to be applied to DNV classed object shall fulfill the material requirements in the applicable DNV class rules.

Issued at **Hamburg** on **2021-05-19**

This Certificate is valid until **2024-06-30**.

DNV local station: **Italy/Malta CMC**

Approval Engineer: **Christian Wildhagen**



for **DNV**

Digitally Signed By: **Roehr, Stefan**

Location: **DNV GL Hamburg, Germany**

Signing Date: **19.05.2021**, on behalf of

**Thorsten Lohmann**  
**Head of Section**

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: AM 311

Revision: 2021-03

www.dnv.com

Page 1 of 2



Job Id: 263.11-004985-3  
Certificate No: AMMM000026W  
Revision No: 1

## Particulars of the approval

---

### Wrought aluminium alloys

Grade	Product	Max. section / wall thickness [mm]	Temper/Heat treatment condition
VL 6082	Section: open profile	25	T6
	Section: closed profile	10	